SECTION 1: IDENTIFICATION				
Trade Name & Synonyms	Sulfur, Treated Rubbermakers Sulfur			
Chemical Name	Sulfur			
CAS Number	7704-34-9	7704-34-9		
Family Name	Element – Sulfur	Element – Sulfur		
Chemical Formula	S ₈	S ₈		
Recommended Use	Rubber compounding and various industrial a	Rubber compounding and various industrial applications		
Restrictions on Use	None known. Keep away from heat sources, s	None known. Keep away from heat sources, sparks, or open flames		
Manufacturer/Supplier	Sales and Technical Services International Sulphur, Inc. P. O. Box 611 Mt. Pleasant, TX 75456 Tel: (903) 577-5500 Fax: (903) 577-5540 isulphur@internationalsulphur.com	Shipping and Receiving International Sulphur, Inc. 1386 North Frontage Road Mt. Pleasant, Texas 75455 Tel: (903) 577-5500 Fax: (903) 577-5540 GPS Coordinates: 33° 9′ 34″ N 95° 03′ 29″ W		
Emergency Assistance	CHEMTREC Tel: (800) 424-9300 within the USA Tel: 001-703-527-3887 outside the USA			

SECTION 2: HAZARDS IDENTIFICATION

GHS Information:

Classification: Skin Irritation, Category 2

OSHA Defined Hazards: Combustible dust

GHS Label Elements

Pictogram (s):



Signal Word: Warning

Hazard Statement: May cause skin irritation. May form combustible dust concentrations in air.

Safety Data Sheet (SDS)

SE	CTION 2: HAZARDS IDENTIFICATION (CONT)
Hazard Statement	H303: May be harmful if swallowed.
	H316: May cause mild skin irritation.
	H320: May cause eye irritation.
	H335: May cause respiratory irritation.
Prevention Statement	P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	P220: Keep away from oxidizing agents.
	P242: Use non-sparking tools when available.
	P243: Take precautionary measures against static discharge.
	P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
	P264: Wash hands thoroughly after handling and before eating.
	P284: In case of inadequate ventilation, wear respiratory protection.
Response Statement	P362: Take off contaminated clothing.
	P363: Wash contaminated clothing before reuse.
	P370+P378: In case of a fire, use water fog, spray, or regular foam to extinguish.
	Do not use a direct water stream.
	P381: Eliminate all ignition sources.
Storage Statement	P402: Store in a dry place.
	P404: Store in a closed container.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization

Mixture

Product	Percentage Contained	CAS Number
Sulfur	>95.0%	7704-34-9
Magnesium Carbonate	< 2.5%	7760-50-1
Tricalcium Phosphate	< 2.5%	7758-87-4
Process Oil (Dedust)	< 1.25%	64742-536 or 64742-52-3

Hazardous Ingredient None

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

Skin

Wash skin thoroughly with mild soap and water. Wash exposed clothing separately before reuse.

- **Eye** Immediately flush eyes with plenty of water for 15 minutes, while holding upper and lower lid apart to insure rinsing of entire eye surface and lids. Do not use boric acid to rinse with. FOR SEVERE IRRITATION, SEEK MEDICAL ATTENTION, preferably an ophthalmologist.
- Inhalation Move victim to fresh air. Watch for signs of an allergic reaction. Use a bronchodilator inhaler if directed by asthma patient. Keep victim warm and quiet. If not breathing, give artificial respiration. If heart has stopped beating, start cardiopulmonary resuscitation (CPR). SEEK MEDICAL ATTENTION.
- Ingestion Give one tablespoon of *Syrup of Ipecac* to induce vomiting. If vomiting does occur, give fluids again. If vomiting has not occurred in twenty minutes, the same dose of *Syrup of Ipecac* may be repeated one additional time. Alternatively, vomiting may be induced by touching the back of the throat with a finger. Do not give anything by mouth to an unconscious or convulsing person. SEEK MEDICAL ATTENTION.

SECTION 4: FIRST AID MEASURES (CONT)

Most Important Symptoms and Effects (Long-Term and Acute)

Refer to Section 11: Toxicological Information

Indication of any Immediate Medical Attention or Special Treatment Needed

Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur.

	SECTION 5: FIREFIGHTING MEASURES
Suitable Extinguishing Media	Water fog, spray, or regular foam. Do not use a direct water stream.
Unsuitable Extinguishing Media	Do not use solid streams of water, which could create sulfur dust clouds and cause an explosion or could move burning sulfur to adjacent areas.
Exposure Hazards	Prevent human exposure to smoke, fumes, or products of combustion (sulfur oxide gases). Evacuate nonessential personnel from the fire area. If large fire, evacuate people downwind from fire. Consider evacuation for ½ mile in all directions.
Advice for Firefighters	Firemen exposed to contaminated smoke should be immediately relieved and checked for symptoms of exposure of toxic gases. This should not be mistaken for heat exhaustion or smoke inhalation. SEEK MEDICAL ATTENTION IMMEDIATELY.
Protective Equipment	Wear full-faced, self-contained breathing apparatus and full protective clothing.
Fire and Explosion Hazards	Fire will rekindle until mass is cooled below 310°F (154°C). Cool surrounding areas with water fog to prevent re-igniting. Sulfur dust is HIGHLY FLAMMABLE. If suspended in air, it will ignite by friction, static electricity, heat, sparks, or flames. Sulfur dust clouds may explode.
Combustion Products	Sulfur oxide gases.
	SECTION 6: ACCIDENTAL RELEASE MEASURES
Personal Precautions	Minor spills such as torn or ruptured containers should be repaired or patched with tape if possible. Place spilled material in a disposable container. Avoid getting dust in eyes.
Protective Equipment	Maintain adequate ventilation. Wear a dust mask when dust is present or a respirator if smoke is present. Wear safety glasses.
Emergency Procedures	As an immediate precautionary measure isolate spills or leak areas. Eliminate all sources of ignition, such as flares, sparks, or flames, in the immediate area. No smoking. Ventilate closed spaces before entering.
Environmental Precautions	Do not allow runoff to enter lakes or waterways.
Containment/Cleanup Measures	Gently sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking, to avoid creating a dust cloud. Place sweepings in an appropriate chemical waste container for reclaiming or disposal in an approved facility. Wash spill site after clean-up is complete.

	SECTION 7: STORAGE AND HANDLING
Precautions for Safe Handling	All handling and conveying equipment should be properly grounded and bonded. Be careful not to create dust. Avoid any conditions that might tend to create a dust explosion. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Keep away from heat, sparks, and flames. Use nonferrous tools, when available, to reduce sparking. Gently sweep or shovel up spilled materials using a natural fiber broom and/or aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.
Conditions for Safe Storage, Inclu	ding any Incompatibilities:
	Containers should be stored in a cool, dry, well-ventilated area. Keep container tightly closed. Store away from flammable materials, sources of heat, flames, and sparks. Separate from chlorates, nitrates, and other oxidizing agents. Exercise due caution to prevent damage to or leakage from container.
Incompatible Materials	Keep away from flammable materials, sources of heat, flame, sparks, chlorates, nitrates and other oxidizing agents.
SECTIO	IN 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION
Engineering Measures/Controls	Maintain adequate ventilation in all areas. No flares or flames in area. Be careful not to create
Personal Protective Equipment Pictograms	dust. Eliminate sources of ignition.
Respiratory	Wear dust masks and use NIOSH/MSHA approved dust respirator if airborne concentrations exceed exposure limits.
Eyes/Face	Wear suitable, protective safety glasses to prevent eye irritation from dust.
Hands	Wash hands thoroughly after handling and before eating or smoking.
Skin/Body	Wear suitable, protective clothing to prevent skin irritation from dust. Wash skin thoroughly after handling and before eating or smoking. Wash contaminated clothing separately before reuse.
Environmental Exposure Controls	Follow best practice for site management and disposal of waste. Avoid release to the environment.
General Industrial Hygiene Considerations	Protective equipment should be used in any situation that may result in hazardous exposure. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Use nonferrous tools to reduce sparking. Sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.

Physical State	Solid, powder form
•	
Appearance	Yellow powder
Formula	S ₈ (Rhombic or monoclinic)
Odor Odorless, or faint odor of rotten eggs	
Odor Threshold No data available	
рН	No data available
Boiling Point	832° F (444° C)
Melting/Freezing Point	118-120°C (244-248°F)
Flash Point	207°C (405°F) Closed Cup
Evaporation Rate	No data available
Flammability May form combustible dust concentrations in a	
Flammable/Explosion Limits Upper: 6.38% (v) Lower: 0.17% (v)	
Vapor Pressure	8 mmHg at 246°C (475°F) 1 mmHg at 183.8°C (362.8°F)
Vapor Density	No data available
Purity	95.0% Min.
Auto-Ignition Temperature	240°C (464°F)
Decomposition Temperature	Does not decompose
Viscosity	Not applicable
Specific Gravity	2.07 @ 70° F
Solubility in Water	Insoluble
Bulk Density	Powder: 33-80 lbs. /ft ³

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

SECTION 10: STABILITY AND REACTIVITY

Stable
Keep from heat sources, sparks, and open flames. Minimize dust generation and accumulation.
Oxidizing agents, copper, copper alloys, steel, chlorates, nitrates.
Oxidizing agents may react violently.
Oxides of sulfur gases produced by burning sulfur.
Will not occur.

	SECTION 11: TOXICOLOGICAL INFORMATION
Likely Routes of Exposure	Inhalation, ingestion, skin contact, and eye contact.
Signs and Symptoms of Overexposure	Nose or throat irritation, coughing, chest discomfort, asthma, difficulty breathing, skin irritation, nausea, vomiting, stinging eye irritation, hives.
Exposure Limits	No exposure limits have been established.
Acute Symptoms and Effects Inhalation	Prolonged inhalation may cause irritation of respiratory tract. Breathing of dust may aggravate asthma and other pulmonary diseases.
Eye Contact	Sulfur dust is an eye irritant.
Skin Contact	No adverse effects. Skin irritation may be aggravated in persons with existing skin lesions.
Ingestion	Ingested sulfur is converted to sulfides in the gastrointestinal tract (GI), and ingestion of 10 to 20 grams has caused irritation of the GI tract and renal injury. Swallowing large amounts may cause nausea and vomiting.

	SECTION	N 11: TO	OXICOLOGICAL IN	FORMATION (CON	NT)
Long-Term Effects	None known to humans				
Toxicity		Oral: >5050 mg/kg (rats)			
-			al: >2020 mg/kg (rats)		
	LC ₅₀	Inhala	ation @ 90%: >5.49-mg/	L air concentration (rats)	
	Skin	Slight	Slightly irritating (rabbits)		
	Eye	-	nal irritation in non-was	hed eyes (rabbits)	
	Sensitization		Reproductive Effects	Developmental Effects	Endocrine Disruptor
	ot Established		Not Established	Not Established	Not Established
	Carcinogenicity		Terat	togenicity	Mutagenicity
This product	t does not contain a	any ingree	dient designated by NTP	, IARC, or OSHA as a proba	ble human carcinogen.
	SE	CTION	12: ECOLOGICAL	INFORMATION	
Toxicity	SE	CTION	12: ECOLOGICAL	INFORMATION	
Toxicity Toxicity to Fish	SE LC ₅₀			INFORMATION w trout) -> 180 mg/l -96h	
	-	Oncol			
Toxicity to Fish	LC ₅₀ LC ₅₀	Oncol Other	rhynchus mykiss (rainbo fish- 866 mg/l -96h	w trout) -> 180 mg/l -96h	
Toxicity to Fish Toxicity to Daphnia	LC ₅₀	Oncol Other	rhynchus mykiss (rainbo	w trout) -> 180 mg/l -96h	
Toxicity to Fish Toxicity to Daphnia and Other Aquatic	LC ₅₀ LC ₅₀	Oncol Other	rhynchus mykiss (rainbo fish- 866 mg/l -96h	w trout) -> 180 mg/l -96h	
Toxicity to Fish Toxicity to Daphnia and Other Aquatic Invertebrates	LC ₅₀ LC ₅₀ EC ₅₀	Oncol Other Daph	rhynchus mykiss (rainbo fish- 866 mg/l -96h	w trout) -> 180 mg/l -96h	
Toxicity to Fish Toxicity to Daphnia and Other Aquatic Invertebrates Ecotoxicity	LC ₅₀ LC ₅₀ EC ₅₀ No data availa	Oncol Other Daph	rhynchus mykiss (rainbo fish- 866 mg/l -96h	w trout) -> 180 mg/l -96h	
Toxicity to Fish Toxicity to Daphnia and Other Aquatic Invertebrates Ecotoxicity Mobility	LC ₅₀ LC ₅₀ EC ₅₀ No data availa No data availa	Oncor Other Daph able able	rhynchus mykiss (rainbo fish- 866 mg/l -96h	w trout) -> 180 mg/l -96h	
Toxicity to Fish Toxicity to Daphnia and Other Aquatic Invertebrates Ecotoxicity Mobility Degradation	LC ₅₀ LC ₅₀ EC ₅₀ No data availa No data availa No data availa	Oncol Other Daph able able able	rhynchus mykiss (rainbo fish- 866 mg/l -96h	w trout) -> 180 mg/l -96h	
Toxicity to Fish Toxicity to Daphnia and Other Aquatic Invertebrates Ecotoxicity Mobility Degradation Bioaccumulation	LC ₅₀ LC ₅₀ EC ₅₀ No data availa No data availa No data availa No data availa	Oncor Other Daph able able able able	rhynchus mykiss (rainbor fish- 866 mg/l -96h inia magna (Water flea)	w trout) -> 180 mg/l -96h -> 5,000 mg/l -48h	uired/not conducted
Toxicity to Fish Toxicity to Daphnia and Other Aquatic Invertebrates Ecotoxicity Mobility Degradation	LC ₅₀ LC ₅₀ EC ₅₀ No data availa No data availa No data availa No data availa	Oncor Other Daph able able able able	rhynchus mykiss (rainbor fish- 866 mg/l -96h inia magna (Water flea)	w trout) -> 180 mg/l -96h	quired/not conducted.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Product Waste Dispose of content and/or container in accordance with local, regional, national and/or international regulations.

Packaging Waste Dispose of content and/or container in accordance with local, regional, national and/or international regulations.

SECTION 14: TRANSPORTATION INFORMATION

Solid sulfur is not regulated if transported in non-bulk packaging (less than 400 kg per package), or if formed to a specific shape, such as prills, granules, pellets, pastilles, or flakes (49 CFR 172.102, Special Provision 30).

US and Canadian Shipments

Bulk containers (packaging) of powdered sulfur of more than 400 kg (880 lbs.) per package

	14.1 UN	14.2 UN Proper	14.3 Transport Hazard Classes	14.4 Packaging	14.5 Environmental
	Number	Shipping Name		Group	Hazards
DOT (Domestic)	NA1350	Sulfur (Sulphur)	9 (Misc. Hazardous Materials)	III	No data available
DOT (International)	UN1350	Sulphur (Sulfur)	4	III	No data available
TDG	UN 1350	Sulfur	4.1	===	No data available

SECTION 14: TRANSPORTATION INFORMATION (CONT)

Other than US and Canadian Shipments

All shipments of powdered sulfur

IMO/IMDG	UN1350	Sulphur (Sulfur)	4.1 (Flammable solid)	III	No data available
IATA/ICAO	UN 1350	Sulfur	4.1	III	No data available

This product is not a Marine Pollutant as defined in 40 CFR Part 172.

Pictograms for Hazard Classes

Powdered sulfur packaging over 400 kg (880 lbs.) only



Special Precautions for User

None specified

	SECTION 15: REGULATORY I	NFORMATION
TSCA	This product is listed on the TSCA Inventory at CA	S Registry Number 7704-34-9.
CERCLA	Comprehensive Environmental Response, Compen	sation, and Liability Act (CERCLA)
		is not subject to any special reporting. We recommend ermine if there are other local reporting requirements.
SARA TITLE III	Superfund Amendments and Reauthorization Act,	Title III
	• Sections 311/312: None. Section 313: No	ne. Section 302: None.
RCRA	Resource Conservation and Recovery Act	
	Not subject to reporting because sulfur is	s not identified as a hazardous waste.
	SECTION 16: OTHER INFO	DRMATION
Last Revision Date	03/28/2019 Preparation Date	05/01/2015
Additional Information	For additional information, contact your technical information, call Georgia Gulf Sulfur Corporation a	sales representative. For additional health and safety at 229-244-0000.
Disclaimer/	THE INFORMATION CONTAINED HEREIN IS BASED	ON THE PRESENT KNOWLEDGE AND DATA AVAILABLE
Statement of Liability		OWEVER, INTERNATIONAL SULPHUR, INC. MAKES NO
		G THE ACCURACY OF THIS DATA OR THE RESULTS TO BE MORE, THIS SHALL NOT CONSITUTE A GUARANTEE FOR
		OT ESTABLISH AND LEGALLY VALIDIFY A CONTRACTUAL
	ANY SPECIFIC PRODUCT FEATURES AND SHALL N	OT ESTABLISH AND LEGALET VALIDIT TA CONTRACTOAL