



# MATERIAL SAFETY DATA SHEET

Salt Sulphur w/Yellow #5, 9605-8

## INTERNATIONAL SULPHUR, INC.

Office: PO Box 611, Mt. Pleasant, TX 75456-0611 ☎ phone (800) 828-7857 ☎ fax (903) 577-5540

Plant: Interstate 30 West, Mt. Pleasant Texas 75455

### EMERGENCY ASSISTANCE:

CHEMTREC (800) 424-9300 (24 Hours)

---

## SECTION 1 CHEMICAL IDENTITY

**Trade Name & Synonyms:** Salt Sulphur w/Yellow #5, 9605-8

**Chemical Name:** Sulphur

**Family Name:** Element - Sulphur

**Chemical Formula:** S<sub>8</sub>

**Appearance:** Odorless, tasteless, bright yellow powder or solid

**CAS Number:** 7704-34-9

**Hazardous Ingredient:** Sulphur

**% by Weight:** 97.5% Min.

---

## SECTION 2 PHYSICAL DATA

**Appearance:** Yellow colored lumps, crystals, powder, or formed shape with FD&C Yellow #5 added

**Odor:** Odorless, or faint odor of rotten eggs

**Purity:** 97.5% Min.

**Formula:** S<sub>8</sub> (Rhombic or monoclinic)

**Vapor Pressure:** 0mmHG at 280°F

**Solubility In Water:** Insoluble

**Specific Gravity:** 2.07 @ 70°F

**Boiling Point:** 832°F (444°C)

**Freezing/Melting Point:** 230-246°F (110-119°C)

**Bulk Density:** Lumps 75-115 lbs./ft<sup>3</sup> Powder 33-80 lbs./ft<sup>3</sup>

---

## SECTION 3 FIRE AND EXPLOSION DATA

**Flashpoint:** 405°F (207.2°C)

**Flammable Limits:** LEL: 35 g/m<sup>3</sup> UEL: 1400 g/m<sup>3</sup>

**Auto-ignition Temperature:** 478-511°F (248-266°C)

**Extinguishing Media:** Water fog, spray, or regular foam. Do not use a direct water stream.

**Burning Sulphur:** Decomposes into TOXIC sulfur oxide gasses such as: **Sulphur dioxide** and **Hydrogen sulfide**.

### ☛ PRIMARY HAZARD:

Sulphur dust suspended in air **ignites** easily, and can cause an **explosion** in confined areas. May be ignited by friction, static electricity, heat, sparks, or flames. Toxic gases will form upon combustion. Bulk/solid forms burn only at moderate rate, whereas dust burns with explosive violence.

### ☛ FIRE:

Wear full-faced, self-contained breathing apparatus and full protective clothing. **Use a water fog** to extinguish fire. Do not use solid streams of water; which could create sulphur dust clouds and cause an explosion or move burning sulphur to adjacent areas. **Fire will rekindle** until mass is cooled below 310°F (154°C). Cool surrounding areas with water fog to prevent re-igniting. Cool containers, tank cars, or trailer loads with flooding quantities of water until well after fire is out. **Evacuate** nonessential personnel from the fire area. If large fire, evacuate people downwind from fire. Isolate for ½ mile in all directions; consider evacuation for ½ mile in all directions. **Prevent human exposure** to smoke, fumes, or products of combustion (sulfur oxide gases). **Firemen exposed** to contaminated smoke should be immediately relieved and checked for symptoms of exposure to toxic gasses. **Seek medical attention immediately!** This should not be mistaken for heat exhaustion or smoke inhalation. These are extremely irritating to the respiratory tract and may cause breathing difficulty and pulmonary edema. Symptoms may be delayed several hours or longer depending upon exposure.

**HAZARD RATING**  
ACUTE HEALTH = 1  
FIRE = 1  
REACTIVITY = 0  
CONTACT = 1

0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

---

#### **SECTION 4 REACTIVITY DATA**

---

**Stability:** Stable

**Conditions to Avoid (Instability):** Keep from heat sources, sparks, and open flames.

**Materials to Avoid (Incompatibility):** Oxidizing agents, may react violently. Corrosive to copper and copper alloys. Damp sulfur will corrode steel.

**Hazardous Polymerization:** Will not occur.

**Hazardous Decomposition Products:** Oxides of sulphur gasses produced by burning sulphur.

---

#### **SECTION 5 HEALTH HAZARDS**

---

Sulphur is essentially non-toxic either through ingestion, inhalation, skin or eye contact. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulphur.

##### **◀ SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Nose or throat irritation, coughing, chest discomfort, asthma, difficulty breathing, nausea, vomiting, stinging eye irritation, skin irritation, hives.

##### **◀ EMERGENCY AND FIRST AID:**

###### **SKIN CONTACT:**

No adverse effects. Skin irritation may be aggravated in persons with existing skin lesions. Wash exposed clothing separately before reuse.

**First Aid:** Wash skin with plenty of mild soap and water.

###### **EYE CONTACT:**

Sulphur dust is an eye irritant. Avoid contact with eyes, especially contact wearers. Wear safety glasses. **First Aid:** In case of contact, immediately flush eyes with plenty of water for a minimum of fifteen minutes. Hold upper and lower lids apart to insure rinsing of the entire eye surface and lids. Do not use boric acid to rinse with; sulphur is an acid irritant. FOR SEVERE IRRITATION, GET MEDICAL ATTENTION, preferably an ophthalmologist.

###### **INHALATION:**

Prolonged inhalation may cause irritation of the respiratory tract. Breathing of dust may aggravate asthma and other pulmonary diseases. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulphur dust. Maintain adequate ventilation in area where dust is present. Wear dust masks and use NIOSH/MSHA approved dust respirator if airborne concentrations exceed exposure limits. **First Aid:** Move patient to fresh air. Watch for signs of allergic reaction. Use a bronchodilator inhaler if directed by asthma patient. Keep victim warm and quiet. If not breathing, clear airway and start mouth-to-mouth resuscitation. If heart has stopped beating, start cardiopulmonary resuscitation (CPR). GET MEDICAL ATTENTION.

###### **INGESTION:**

Ingested sulphur is converted to sulfides in the gastrointestinal tract, and ingestion of 10 to 20 grams has caused irritation of the GI tract and renal injury. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulphur. Swallowing large amounts may cause nausea and vomiting. Do not eat sulphur. **First Aid:** For large amounts ingested, if the victim is conscious and alert, give two or more glasses of water to drink. If available, give one tablespoon of Syrup of Ipecac to induce vomiting. If vomiting does occur, give fluids again. If vomiting has not occurred in twenty minutes, the same dose of Syrup of Ipecac may be repeated one additional time. Alternatively, vomiting may be induced by touching the back of the throat with a finger. Do not give anything by mouth to an unconscious or convulsing person. GET MEDICAL ATTENTION.

###### **EXPOSURE LIMITS:**

No exposure limits have been established.

###### **TOXICOLOGY:**

**Oral LD<sub>50</sub> (Rats):**>5050 mg/kg body weight

**Dermal LD<sub>50</sub> (Rats):**>2020 mg/kg body weight

**Inhalation @ 90% LC<sub>50</sub> (Rats):**>5.49 mg/L air concentration

**Skin Effects (Rabbits):** Slightly irritating

**Eye Effects (Rabbits):** Minimal irritation in non-washed eyes

###### **CARCINOGENICITY, TERATOGENICITY, MUTAGENICITY:**

This product does not contain any ingredient designated by NTP, IARC, or OSHA as a probable human carcinogen.

---

## SECTION 6 PRECAUTIONS FOR SAFE HANDLING AND USE

---

### STORAGE:

Containers should be stored in a cool, dry, well-ventilated area. Keep container tightly closed. Store away from flammable materials, sources of heat, flame and sparks. Separate from chlorates, nitrates and other oxidizing agents. Exercise due caution to prevent damage to or leakage from container.

### ☛ EXPLOSION HAZARD:

Avoid any conditions that might tend to create a dust explosion. Be careful not to create dust. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Keep away from heat, sparks and flames. Use nonferrous tools to reduce sparking. Sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.

### ☛ SMALL or LARGE SPILLS:

No flares or flames in area. No smoking. Danger of dust explosion near sparks. Sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking. Place sweepings in an appropriate chemical waste container for reclaiming or disposal in an approved facility. Wash spill site after clean up is complete. Wear protective clothing during clean up: safety glasses, rubber gloves, impervious clothing, dust mask or respirator.

---

## SECTION 7 PROTECTIVE EQUIPMENT

---

### WORK AREA:

Protective equipment should be used during the following procedures:

- Manufacture or formulation of this product.
- Repair and maintenance of contaminated equipment.
- Clean up of leaks and spills.
- Any situation that may result in hazardous exposure.

Maintain adequate ventilation and wear a respirator or a dust mask to prevent inhalation. Wear suitable, protective clothing and safety glasses to prevent skin and eye irritation from dust. Maintain a sink, safety shower and eyewash fountain in the work area. Wash skin thoroughly after handling and before eating or smoking. Wash contaminated clothing separately before reuse.

---

## SECTION 8 DOT AND REGULATORY INFORMATION

---

### TSCA:

This product is listed on the TSCA Inventory at CAS Registry Number 7704-34-9.

### CERCLA:

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA). If this product is accidentally spilled, it is not subject to any special reporting. We recommend that you contact state and local authorities to determine if there are other local reporting requirements.

### SARA TITLE III:

Superfund Amendments and Reauthorization Act, Title III, Sections 311/312: Hazard Category: Delayed Health. Section 313: None. Section 302: None.

### RCRA:

Resource Conservation and Recovery Act: not subject to reporting because sulfur is not identified as a hazardous waste.

### SHIPPING CLASSIFICATION:

Solid sulfur is not regulated if transported in non-bulk packaging, (less than 400kg per package) or if formed to a specific shape, such as prills, granules, pellets, pastilles, or flakes. [49CFR 172.102, Special Provision 30]

**DOT DOMESTIC:** Bulk Packaging – Powdered Sulphur Only

**Shipping Name:** Sulphur (Sulfur)

**Hazard Class:** 9 (Misc. Hazardous materials)

**ID Number:** NA1350

**Packing Group:** III

**Label:** Class 9

**Placard:** Class 9

**Shipping Description:** Sulphur, 9, NA1350, III

**Hazardous Substance/Rq:** Not Applicable

*Shipping description may be modified by placing the UN or NA number as the first element. This order becomes mandatory on January 1, 2013.*

*Alternative shipping description may be:*

*NA1350, Sulphur, 9, III*

**DOT INTERNATIONAL:** Bulk Packaging – Powdered Sulphur Only (Canada)  
**Shipping Name:** Sulphur (Sulfur)  
**Hazard Class:** 4.1 (Flammable Solid)  
**ID Number:** UN1350  
**Packing Group:** III  
**Label:** Class 4, Flammable Solid  
**Placard:** Class 4 (Flammable Solid)  
**Shipping Description:** UN1350, Sulphur, 4.1, III  
**Hazardous Substance/Rq:** Not Applicable

**IMDG:** Powdered Sulphur – all packages  
**Shipping Name:** Sulphur (Sulfur)  
**Hazard Class:** 4.1 (Flammable Solid)  
**ID Number:** UN1350  
**Packaging Group:** III  
**Label:** Class 4, Flammable Solid  
**Placard:** Class 4 (Flammable Solid)  
**Shipping Description:** UN1350, Sulphur, 4.1, III  
**Hazardous Substance/Rq:** Not Applicable

This product is not a Marine Pollutant as defined in 40 CFR part 172.

---

*FOR ADDITIONAL INFORMATION, CONTACT YOUR TECHNICAL SALES REPRESENTATIVE. FOR ADDITIONAL HEALTH & SAFETY INFORMATION, CALL INTERNATIONAL SULPHUR, INC. AT (903) 577-5500.*

---

*THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, INTERNATIONAL SULPHUR, INC. MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. INTERNATIONAL SULPHUR, INC. ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.*

**DATE OF ISSUE: MAY 31, 2011**